

# Airpad Select Glass

## Product Range



Select

## Features



## Applications



## Filter Class

G

Coarse



## KEY FACTS

- Compact design for simple storage, installation, handling and removal
- Available in a wide range of sizes
- Heavy duty, moisture-resistant design

## DESIGN

Glass fiber media in a heavy duty, moisture-resistant chipboard case, which is creased prior to folding to eliminate moisture ingress.

## APPLICATIONS

Prefiltration in general HVAC systems to protect plant room equipment and duct linings, and to extend the life of higher cost secondary filters.

# Airpad Select Glass

## PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Flow Rate	Pressure Drop
	EN 779	ISO 16890	mm	m <sup>3</sup> /h	Pa
800210021431	G3	Coarse 60%	287 x 596 x <b>22</b>	1100	38
800210021430	G3	Coarse 60%	296 x 296 x 22	580	38
800210021428	G3	Coarse 60%	395 x 624 x 22	1600	38
800210021429	G3	Coarse 60%	496 x 624 x 22	2000	38
800210020866	G3	Coarse 60%	287 x 596 x <b>47</b>	1100	40
800210020871	G3	Coarse 60%	296 x 296 x 47	450	40
800210020868	G3	Coarse 60%	395 x 624 x 47	1700	40
800210020842	G3	Coarse 60%	596 x 596 x 47	2300	40
800210020679	G3	Coarse 60%	287 x 596 x <b>98</b>	1100	60
800210020714	G3	Coarse 60%	296 x 296 x 98	600	60
800210020709	G3	Coarse 60%	395 x 624 x 98	1650	60
800210020678	G3	Coarse 60%	596 x 596 x 98	2400	60

## SPECIFICATION

Recommended air velocity	1.85 m/s	Recommended final pressure drop	250 Pa
Heat resistance	Max. 100 °C	Moisture resistance	80 % rel. humidity
Regenerable	No	Incinerable	Yes

## OPTIONS

Frame	Moisture-resistant cardboard (standard), or metal (optional)
-------	--