

Airpanel Select

Synthetic pleated filter

Product Range



Applications



Filter Class

G

Coarse



KEY FACTS

- Compact design
- Specially-finished support grid prevents oxidization
- Chemically-bonded media ensures pleat stability
- Simple installation and handling

DESIGN

Pleated, synthetic filter media laminated onto an expanded diamond grid, which features a special finish to prevent oxidization.

APPLICATIONS

Prefiltration for air conditioning and ventilation equipment and/or systems highly effective with coarse dust.

Airpanel Select

Synthetic pleated filter

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Flow Rate	Pressure Drop
	EN 779	ISO 16890	mm	m ³ /h	Pa
800220014387	G4	Coarse 65%	287 x 596 x 47	965	30
800220014356	G4	Coarse 65%	296 x 296 x 47	494	30
800220014366	G4	Coarse 65%	395 x 624 x 47	1390	30
800220014459	G4	Coarse 65%	448 x 448 x 47	1130	30
800220014367	G4	Coarse 65%	496 x 624 x 47	1744	30
800220014389	G4	Coarse 65%	596 x 596 x 47	2000	30
				3400	80
800220014005	G4	Coarse 75%	287 x 596 x 98	964	25
800220015247	G4	Coarse 75%	296 x 296 x 98	494	25
800220014031	G4	Coarse 75%	395 x 624 x 98	1390	25
800220014065	G4	Coarse 75%	496 x 624 x 98	1744	25
800220015251	G4	Coarse 75%	596 x 596 x 98	2000	25
				3400	65

SPECIFICATION

Recommended air flow	Flow rate ± 25 %	Recommended final pressure drop	200 Pa (max. 250 Pa)
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity / 90 % cardboard frame
Regenerable	No	Incinerable	Yes, except for metal frames

OPTIONS

Frame	Moisture-resistant cardboard or metal
-------	---------------------------------------