


Nanoclass Deeppleat Select

Product Range



Select

Features



Applications



Filter Class

E

H



KEY FACTS

- Available in a variety of frame materials
- Extremely long service life
- Suitable for heavy-duty operation
- Robust pleating technology
- Optional handle available

DESIGN

Ultra-fine glass fiber media with aluminum separators to ensure pleat spacing and stability.

APPLICATIONS

Designed for supply, recirculation and exhaust air, where the highest demands are placed on air purity and filter life. Typical industries include pharmaceutical, food, optics, biotechnology, operating theaters and nuclear.

Nanoclass Deeppleat Select

PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	EN 1822	mm	m ³ /h	Pa
800530024248	E11	305 x 610 x 150	1050	250
800530024251	E11	457 x 610 x 150	1580	250
800530024245	E11	610 x 610 x 150	2100	250
800530024246	H13	305 x 610 x 150	530	250
800530024249	H13	457 x 610 x 150	800	250
800530024243	H13	610 x 610 x 150	1050	250
800530024247	H14	305 x 610 x 150	500	250
800530024250	H14	457 x 610 x 150	750	250
800530024244	H14	610 x 610 x 150	1000	250
800530024241	E11	305 x 610 x 292	2100	250
800530024242	E11	457 x 610 x 292	3160	250
800530024240	E11	610 x 610 x 292	4200	250
800530024224	H13	305 x 610 x 292	1050	250
800530024226	H13	457 x 610 x 292	1580	250
800530024222	H13	610 x 610 x 292	2100	250
800530024225	H14	305 x 610 x 292	1000	250
800530024227	H14	457 x 610 x 292	1500	250
800530024223	H14	610 x 610 x 292	2000	250

SPECIFICATION

Recommended air flow	Flow rate ± 10 %	Recommended final pressure drop	450 Pa (max. 800 Pa)
Heat resistance	Max. 120 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	No

OPTIONS

Frame	MDF, galvanized steel or stainless steel
Gasket	Continuous polyurethane or flat EPDM, 1 or 2 sides
Grid	Galvanized steel or stainless steel, 1 or 2 sides
Header depth	25 mm or 20 mm