

# Nanoclass Tube Pro

Product Range



Features



Applications



Filter Class



KEY FACTS

- Compact, space-saving designs
- Low pressure drop
- Available in a wide variety of sizes and casing types
- Large filter area
- Individually tested and leak-free
- Corrosion resistant

DESIGN

Micro-glass filter media enclosed within an aluminum protection grid, attached to a ring and base made of Resocel.

APPLICATIONS

Filtration of bacteria, viruses or general contaminants suspended in air, compressed air or gases.

# Nanoclass Tube

## Pro

### PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	EN 1822	mm	m <sup>3</sup> /h	Pa
800560000054	H13	155 x 50	25	200
800560000033	H13	155 x 100	55	200
800560000035	H13	155 x 150	80	200
800560000054	H13	155 x 200	110	200
800560000069	H13	200 x 50	40	200
800560000055	H13	200 x 100	70	200
800560000055	H13	200 x 150	115	200
800560000059	H13	200 x 200	150	200
800560000057	H13	200 x 300	200	200
800560000058	H13	200 x 400	250	200

### SPECIFICATION

Recommended air flow	Flow rate ± 10 %	Recommended final pressure drop	1000 Pa
Heat resistance	Max. 90 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes

### OPTIONS

Frame	Galvanized or stainless steel
-------	-------------------------------